

## P3.9 MM PIXEL PITCH

Pixel Pitch (mm)	3.906
Pixel Density (pixels/m <sup>2</sup> )	65,536
LED type - 3-in-1 Copper	SMD2020 Copper lead
Drive Mode	1/21
Gray Scale	14 bit
Refresh Rate	3840 Hz
Receiving Card	Novastar A5s plus
Module Resolution	64 x 64
Module Dimension	250 x 250mm
Cabinet Resolution	W128 x H128
Cabinet Dimension	W500 x H500 x 69 mm
Cabinet Type and Material	Die-Cast Aluminium
Cabinet Weight	8kg / 17.6 lbs
Viewing Angle	H160°/V160°
Brightness (Calibrated)	≥800 nits
Operating Power Source	100-240 VAC/50-60 Hz
Max Power Consumption Watts/ Panel	150
Avg Power Consumption Watts P/Panel	45
Max Power Consumption 208 VAC	0.72
Avg Power Consumption 208 VAC	0.22
Max Power Consumption 110 VAC	1.36
Avg Power Consumption 110 VAC	0.41
BTU/H @ Max Power Consumption	410
BTU/H @ Avg Power Consumption	123
Operating Temp/Humidity	-20°~ 50°C, 10~90% RH
Storage Temp/Humidity	-40°~ 60°C, 10~90% RH
Certifications /Listings	ETL
IP Rating	IP43
Life Span	100,000 h
Serviceability	Front/Rear
Curvable	Concave and convex 2.5°, 5°

