

P1.9 MM PIXEL PITCH

Pixel Pitch (mm)	1.95
Pixel Density (pixels/m ²)	65,536
LED type - Copper	SMD1212
Drive Mode	1/21
Gray Scale	≥14bits
Refresh Rate	3840 Hz
Receiving Card	Novastar A5s plus
Module Resolution	128 x 128
Module Dimension	250 x 250mm/0.98 x 0.98in
Cabinet Resolution	W256 x H256
Cabinet Dimension	W500 x H500 x 69 mm
Cabinet Type and Material	Die-Cast Aluminium
Cabinet Weight	8kg / 17.6 lbs
Viewing Angle	H160°/V160°
Brightness (Calibrated)	≥800 nits
Operating Power Source	100-240 VAC/50-60 Hz
Max Power Consumption Watts/ Panel	160
Avg Power Consumption Watts P/Panel	80
Max Power Consumption 208 VAC	0.77
Avg Power Consumption 208 VAC	0.38
Max Power Consumption 110 VAC	1.45
Avg Power Consumption 110 VAC	0.73
BTU/H @ Max Power Consumption	437
BTU/H @ Avg Power Consumption	218
Operating Temp/Humidity	-20°~ 50°C, 10~90% RH
Storage Temp/Humidity	-40°~ 60°C, 10~90% RH
Certifications /Listings	ETL
IP Rating	IP43
Life Span	100,000 h
Serviceability	Front/Rear
Curvable	Concave and convex 2.5°, 5°

